

NASA/TM—2003-211691

AIAA-2002-3589



An Updated Zero Boil-Off Cryogenic Propellant Storage Analysis Applied to Upper Stages or Depots in an LEO Environment

David Plachta
Glenn Research Center, Cleveland, Ohio

Peter Kittel
Ames Research Center, Moffett Field, California

June 2003

The NASA STI Program Office . . . in Profile

Since its founding, NASA has been dedicated to the advancement of aeronautics and space science. The NASA Scientific and Technical Information (STI) Program Office plays a key part in helping NASA maintain this important role.

The NASA STI Program Office is operated by Langley Research Center, the Lead Center for NASA's scientific and technical information. The NASA STI Program Office provides access to the NASA STI Database, the largest collection of aeronautical and space science STI in the world. The Program Office is also NASA's institutional mechanism for disseminating the results of its research and development activities. These results are published by NASA in the NASA STI Report Series, which includes the following report types:

- **TECHNICAL PUBLICATION.** Reports of completed research or a major significant phase of research that present the results of NASA programs and include extensive data or theoretical analysis. Includes compilations of significant scientific and technical data and information deemed to be of continuing reference value. NASA's counterpart of peer-reviewed formal professional papers but has less stringent limitations on manuscript length and extent of graphic presentations.
- **TECHNICAL MEMORANDUM.** Scientific and technical findings that are preliminary or of specialized interest, e.g., quick release reports, working papers, and bibliographies that contain minimal annotation. Does not contain extensive analysis.
- **CONTRACTOR REPORT.** Scientific and technical findings by NASA-sponsored contractors and grantees.

- **CONFERENCE PUBLICATION.** Collected papers from scientific and technical conferences, symposia, seminars, or other meetings sponsored or cosponsored by NASA.
- **SPECIAL PUBLICATION.** Scientific, technical, or historical information from NASA programs, projects, and missions, often concerned with subjects having substantial public interest.
- **TECHNICAL TRANSLATION.** English-language translations of foreign scientific and technical material pertinent to NASA's mission.

Specialized services that complement the STI Program Office's diverse offerings include creating custom thesauri, building customized databases, organizing and publishing research results . . . even providing videos.

For more information about the NASA STI Program Office, see the following:

- Access the NASA STI Program Home Page at <http://www.sti.nasa.gov>
- E-mail your question via the Internet to help@sti.nasa.gov
- Fax your question to the NASA Access Help Desk at 301-621-0134
- Telephone the NASA Access Help Desk at 301-621-0390
- Write to:
NASA Access Help Desk
NASA Center for AeroSpace Information
7121 Standard Drive
Hanover, MD 21076



An Updated Zero Boil-Off Cryogenic Propellant Storage Analysis Applied to Upper Stages or Depots in an LEO Environment

David Plachta
Glenn Research Center, Cleveland, Ohio

Peter Kittel
Ames Research Center, Moffett Field, California

Prepared for the
38th Joint Propulsion Conference and Exhibit
cosponsored by AIAA, ASME, SAE, and ASEE
Indianapolis, Indiana, July 7-10, 2002

National Aeronautics and
Space Administration

Glenn Research Center

Acknowledgments

The authors want to acknowledge Robert Christie and Dale Robinson of ZIN Technologies, Inc. for their design integration work on the Protoflight ZBO Development Test Article, and Ken Mellott and Steve Geng of NASA GRC for their radiator analysis.

This report is a formal draft or working paper, intended to solicit comments and ideas from a technical peer group.

This report contains preliminary findings, subject to revision as analysis proceeds.

Available from

NASA Center for Aerospace Information
7121 Standard Drive
Hanover, MD 21076

National Technical Information Service
5285 Port Royal Road
Springfield, VA 22100

Available electronically at <http://gltrs.grc.nasa.gov>

AN UPDATED ZERO BOIL-OFF CRYOGENIC PROPELLANT STORAGE ANALYSIS APPLIED TO UPPER STAGES OR DEPOTS IN AN LEO ENVIRONMENT

David Plachta

National Aeronautics and Space Administration
Glenn Research Center
Cleveland, Ohio 44135

Peter Kittel

National Aeronautics and Space Administration
Ames Research Center
Moffet Field, California 94035

Abstract

Previous efforts have shown the analytical benefits of zero boil-off (ZBO) cryogenic propellant storage in launch vehicle upper stages of Mars transfer vehicles for conceptual Mars Missions. However, recent NASA mission investigations have looked at a different and broad array of missions, including a variety of orbit transfer vehicle (OTV) propulsion concepts, some requiring cryogenic storage. For many of the missions, this vehicle will remain for long periods (greater than one week) in low earth orbit (LEO), a relatively warm thermal environment. Under this environment, and with an array of tank sizes and propellants, the performance of a ZBO cryogenic storage system is predicted and compared with a traditional, passive-only storage concept. The results show mass savings over traditional, passive-only cryogenic storage when mission durations are less than one week in LEO for oxygen, two weeks for methane, and roughly 2 months for LH2. Cryogenic xenon saves mass over passive storage almost immediately.

Introduction

NASA has redirected the Integrated In-Space Transportation Program (IISTP) from Code R management to Code S; accordingly, the propulsion elements under development are aligned with science and exploration mission concepts. Several propulsion concepts being studied for these missions could involve cryogenic propellant storage; specifically, advanced chemical, nuclear bi-modal, solar thermal, and perhaps solar electric propulsion, particularly if it is combined with an advanced chemical propulsion assist. In addition to these concepts for IISTP, a propellant depot called the Hybrid Propulsion Module (HPM) led by NASA Langley Research Center, includes cryogenic propellants. These concepts would all involve orbit transfer from LEO, some to higher earth orbits and most to other planets or destinations. The duration of the storage for all of these concepts varies from minutes to years; the

purpose of this paper is to estimate the durations where the ZBO storage approach begins to reduce mass of the OTV. This estimation is based on scaling parameters determined from testing as well as analysis and design. The ZBO design work referenced is from a Protoflight ZBO Development Test Article (configuration shown in figure 1), which includes a flight cryocooler integrated with a propellant tank and a radiator, in a LEO simulated thermal environment.

The designs and estimations are guides for propulsion and mission design engineers in their evaluations and trade-studies involving cryogenic propellant usage. Besides helping them, this paper advances several details of the ZBO storage concept from previous studies.^{1,2} First, a detailed cryocooler integration design is shown and associated temperature drops are included, as they represent losses that require the cryocooler to operate at a lower temperature. Secondly, a tank mixer has been added to force flow across the heat exchanger coupled to the cryocooler. In addition, a radiator and associated thermal analysis is incorporated to reject the heat from the cryocooler. Finally, a look into the appropriate number of MLI layers for a ZBO tank is described.

Thermal Model

The following discussions on the analysis form the basis of the thermal model used in the analysis. Several parts are repeated from reference 1 for clarity, but the bulk of the work is based on additional research and design.

Cryocooler Model

The cryocooler model used is updated from reference 1. While the hydrogen cryocooler is again modeled using two cryocoolers (for simplicity), in this approach the first cryocooler is used to reduce the temperature of a tank shield to a typical intermediate value of a first stage of a two-stage cooler; the second cryocooler removes the remaining heat that enters the tank through that shield. Reference 1, on the other




Figure 1.—Three-dimensional drawing of Proto-flight Development ZBO Test Article.

hand, incorporated a shield cryocooler in addition to a second cryocooler that removes all the heat entering the tank. The reference 1 advantage is the independence of each stage, while its disadvantage is somewhat heavier second cryocooler and more power. The revised approach disadvantage is that the stages are dependent on one another, and a high thermal load on the first stage could dwindle the performance of the second stage. Accordingly, we are assuming that the cryocooler stages and integration could be designed to match the OTV cryogenic propellant stage performance.

Unchanged from reference 1, the cryocooler sizing relationships are based on Strobridge, with modifications to account for advances in the last 25 years³ are as follows:

$$\dot{Q}_{ip} = \dot{Q}_c (T_h - T_c) (T_c \eta 10^\Sigma)^{-1} \quad (1)$$

where

$$\Sigma = -1.7359 + 0.59998 \log(\dot{Q}_c) - 0.14740 \log(\dot{Q}_c)^2 + 0.021323 \log(\dot{Q}_c)^3 - 0.0012502 \log(\dot{Q}_c)^4 \quad (2)$$

wherein \dot{Q}_{ip} is the electrical input power, \dot{Q}_c is the cooling power, T_h is the cryocooler heat rejection

temperature, T_c is the cryocooler coldhead temperature, and η is the improvement factor. The values used for η were 2.5 for CH_4 and O_2 tanks and 2.0 for H_2 tanks. These factors are estimated based on current and projected near term capabilities.^{4,5} Similarly, the mass of cryocooler is based on Strobridge's correlations adjusted by a factor of 0.2 to account for recent advances:

$$m = 0.2 \dot{Q}_c^{0.7} [(T_h - T_c) / T_c]^{1.45} \quad (3)$$

Additionally, cryocooler controller mass is included for the first time. It is estimated to be 1.4 times that of the cryocooler itself, based upon existing flight controllers.

Integration Loss and Vapor Cooled Shield

Assumption

Another update to the thermal model is the addition of an integration loss, due to physical integration of the cryocooler into the propellant tank. The loss used is based on the integration design of the flight cryocooler in the Protoflight ZBO Development Test Article, which uses liquid nitrogen as the working fluid and transfers 6.8 watts of heat to the cryocooler. The temperature drop was 8.5K (see figure 2 and table 1).




Figure 2.—Integration design connects cryocooler to propellant tank lid.

Integration Element	Temperature Drop, K
Convection drop	0.28
Fin conduction	0
Fin-wall interface	<i>0.5</i>
Evaporator wall	0.005
Evaporator	1.3
Condenser	0.98
Condenser wall	0.004
Wall-saddle interface	<i>0</i>
Saddle	0.34
Saddle-s-link interface	<i>0.5</i>
S-link	4.08
S-link to coldhead interface	<i>0.5</i>
Total	8.5

Table 1. A listing of the components and interfaces with their calculated or assumed (in italics) temperature drops for integration into a LN2 propellant tank for a protoflight test with an estimated 6.8 watts heating rate.

This drop causes the cryocooler coldhead to operate that much below the propellant bulk liquid temperature, as follows:

$$T_c = T_{\text{bulk}} - T_{\text{drop}}. \quad (4)$$

This is represented as inefficiency according to the following equation:

$$(1-\eta) = (T_{\text{bulk}} - T_c) * (T_h/T_{\text{bulk}}) / (T_h - T_{\text{bulk}}). \quad (5)$$

For the Protoflight ZBO Development Test Article, (1-η) is 12%, which is used in this analysis. While this term would vary slightly with T_{bulk} depending on the fluid, those variations were not included.

The loss for integrating a cryocooler with a liquid hydrogen propellant tank has an additional part because of liquid hydrogen cryocooler's two stages, the intermediate stage (first stage) in addition to the cold head (second stage). The second stage loss is 12%, as discussed above. The first stage loss is more uncertain as it will be integrated differently, perhaps with a heat pipe to cool an oxidizer tank or tank penetrations such as feed lines or tank support struts, or in conjunction with a vapor-cooled shield to reduce the temperature of the insulation. A check on the analysis shows a vapor-cooled shield to be quite heavy, yet it slightly reduces the overall system mass and we have assumed its use around the tank. Because it is much larger and the heat travels further

than the heat exchanger attached to the second stage, it will have a greater temperature drop. Correspondingly, a larger loss of 20% was arbitrarily assumed to integrate the shield with the first stage.

The shield mass used is based on a vapor-cooled shield design. Shield valving and controls were not considered.

Mixer Heat Assumption

A mixer, which is integrated into the tank to de-stratify the propellant and force convective heat transfer across the heat exchanger (as shown in figure 1), is also represented in the analysis and is an upgrade from reference 1. Heat inputs from de-stratification mixers for existing flight and ground designs and tests were investigated. Analysis for the COLD-SAT⁶ flight experiment, and the analysis for our Protoflight ZBO Development Test Article test show that much less jet momentum (and, correspondingly, mixer power) is needed for flight applications. Analyses published by Poth and Van Hook⁷ supports this conclusion. They showed that jet momentum for low Bond numbers, which occur in low gravity environments, is a function of jet inertial surface tension forces. For ground tests with the comparatively much higher acceleration force of gravity, large Bond numbers ($N_{Bo} > 10$) occur. In this case, jet momentum is a function of jet inertia forces and body forces caused by gravity.

Applying that analysis to 2.2 meter diameter tanks (additional assumptions include 97% full tank with 0.18 m jet nozzle height), the jet momentum for LO₂ ground applications is 64 times that for flight, and for LH₂ propellants it is 42 times greater. Therefore, the mixer heat added to the tank for flight applications is assumed to be 1/64th (for O₂) and 1/42nd (for H₂) that of our ZBO ground demonstration, which was found to be 16% of the total heat added to the tank. Correspondingly, the submerged mixer heat added for this analysis is assumed to be 0.25% (O₂, CH₄, and Xe) and 0.38% (for H₂) of the heat entering the tank.

Heat Rejection Assumption

The mixer heat (which is almost insignificant) is added to the environmental heat entering the tank and must be removed by the cryocooler and ultimately rejected by its radiator. The lower the rejection temperature is, the higher the Carnot efficiency of the system. The radiator design, cryocooler input power, environmental temperature, vehicle orientation, and the propellant tank heat load directly affect this temperature.

For the Protoflight ZBO Development Test Article, an ANSYS thermal model found the heat rejection temperature to be 50K above the environmental temperature for the radiator design used. Flight radiator designs will be more efficient and, according to the cryocooler manufacturer,⁸ this design temperature could be improved for flight to roughly 30K, which was used in this analysis.

MLI Assumption

Another variation from reference 1 is that the number of MLI layers used was eliminated as a variable. This was done to present the results more simply; also, by using a spreadsheet analysis it was possible to narrow in on the appropriate number of layers for each propellant studied. This was found by adding up the predicted passive and ZBO thermal storage mass, that is, the tank, insulation, propellant, and boil-off mass for the passive case and the tank, insulation, propellant, solar array, and radiator mass for the ZBO case for a given number of MLI layers, then vary the quantity of layers and narrow in on the lowest mass results at the point where the passive and ZBO masses were equal. This was done for the average tank diameter used for each propellant. For the LH2 case, the layers were divided up such that 2/3rds (or 30 layers) covered the vapor-cooled shield attached to the 1st stage and the rest blanketed the propellant tank. This proportion was chosen because the MLI layer 2/3rds the way through the thickness is estimated to be close to the temperature of the shield. These results are shown in table 2.

Propellant	MLI Layers Used
LH ₂	45
LO ₂	30
LCH ₄	30
LXe	15

Table 2. The initialization of the number of MLI layers that result in the lowest thermal storage mass for a given propellant.

Passive Analysis Algorithm

The reference 1 algorithm used for tank mass and volume growth estimating was also rewritten, to eliminate a program bug that made it difficult to run.

This algorithm determines the necessary tank growth to accommodate boil-off. This solution was iterative, that is, as the tank grew to accommodate boil-off tank volume and surface area increased, causing the boil-off to increase a little more. A small portion (1/100th) of the volume for that boil-off was added to the tank volume and iterated upon as long as it still increased. When it stopped increasing, the tank was at the appropriate size to accommodate boil-off and the iteration stopped.

Variables

The most significant variable in the study was tank diameter (note that all tanks are assumed spherical). The diameters used have been typical propellant tank sizes used in HEDS analysis and in various transportation studies. They are shown in table 3.

Tank Diameters Considered, meters			
LO ₂	LCH ₄	LXe	LH ₂
1.2	1.2	1.2	1.2
2.2	2.2	2.2	2.2
3.3	3.3		3.3
4.4	4.4		4.4
			5.5

Table 3. The tank diameters considered in the trade space, shown for each propellant. Larger tank sizes for higher density fluids were not considered.

Another variable was the power and heat rejection system mass. It is possible and likely for some missions that this mass would be coupled with other much larger vehicle power and heat rejection requirements, thus, results are shown with and without it.

The last variable discussed is tank growth, necessary to accommodate boil-off. For passive solutions, larger tanks mean more tank and insulation mass. This effect is shown in bar graph form. A literature search found no previous analysis that included this very significant mass.

Summary of Assumptions

Because of the many parameters used and the significant changes from reference 1, table 4 is included to summarize the analysis approach.

Parameter	Assumed Value	Basis	Variation from Ref. 1
Tank Mass per Surface Area	5.4 kg/m ² for H ₂ , O ₂ , CH ₄ , 20 kg/m ² for Xe	Analysis by MSFC mission analyst. Reflects a 25% mass reduction in present tank designs.	Xe not previously analyzed. Its high tank density was assumed because of Xe's high density.
Insulation Mass per Surface Area	0.02 kg/m ² /layer	Based on actual design for flight at MSFC ⁹	Includes mass for purge bag for LH2 and LO2
Tank Ullage	3%	Prevent tank rupture	None
Tank Residual	2%	Inaccessible propellant	None
Fluid Properties		Sat. liquid at 0.2 MPa	None
Environmental LEO Temperature	243K	Avg. temp. of Earth and Sun oriented orbits. From radiation analysis of a representative vehicle.	250K
Margin	5%	Cryocooler sized to remove 5% more heat than enters tank.	0%
Heat Rejection Temperature	273K	See text.	250K
Insulation Heating Rate	Lockheed Equation (include equation) times 1.8	1.8 is a compensating factor, which correlates with reference 3 testing results.	Thicker MLI blankets not considered
Penetration Heating	$\dot{Q} = 1.28 \times 10^{-4} (f/35)^2 (T/250)^{2.3}$ m for O ₂ , CH ₄ , and Xe tanks, $\dot{Q} = 2.70 \times 10^{-4} (f/35)^2 (T/250)^{1.6}$ m for H ₂ tanks f = frequency T = heat rejection temp.	S glass epoxy struts ¹⁰	None
Mixer Heat	0.25% of tank heating for LO ₂ , LCH ₄ , LXe; 0.38% for LH ₂	See text	Not included
Integration Loss	12% or 20%	See text	Not included
Cryocooler controller	1.4 times cryocooler mass	Existing flight controllers	Not included

Table 4. A summary of assumptions used in analysis.

Results

All results shown use the thermal storage mass, which is defined as follows:

Passive: Tank, insulation, propellant, boil-off, and tank/insulation growth.

ZBO: Tank, insulation, propellant, cryocooler, solar array, radiator.

The first graph (figure 3) includes passive and ZBO thermal storage mass predictions for oxygen as a function of storage duration, or the days in LEO with cryogens, regardless of the number of engine burns.

That graph is repeated twice more, for methane (fig. 4) and hydrogen (fig. 5). From those graphs and additional runs with xenon, the equal mass lines were constructed and are shown (fig. 6). These are the storage duration's where the passive and ZBO masses are equal; durations longer than these are predicted to reduce mass for ZBO; durations shorter would benefit if passive storage was used.

The bar graph in figure 7 shows the effect if power systems were available to power the cryocooler. Eliminating that mass from the trade reduces the




Figure 3.—Passive and ZBO cryogenic thermal storage mass versus duration for LO₂ storage in 2.2-m-diam tank.




Figure 4.—Passive and ZBO cryogenic thermal storage mass versus duration for LCH₄ storage in 2.2-m-diam tank.




Figure 5.—Passive and ZBO cryogenic thermal storage mass versus duration for LH₂ storage in 3.3-m-diam tank.




Figure 6.—Graphical composite that shows duration at which ZBO and passive storage mass is equal for a given tank size. Durations longer than these are predicted to save mass if ZBO is incorporated.




Figure 7.—Equal mass variation if power system is available and mass not included. If so, ZBO applicable for much shorter durations.




Figure 8.—Equal mass variation if tank growth to accommodate boil-off is not considered. If not, passive thermal control mistakenly appears to reduce mass to much longer storage duration than it should.

equal mass line's days in LEO substantially. Next, figure 8 shows the effect if tank growth was not considered. If not, then ZBO would not nearly be so beneficial.

Discussion

The results are surprising. The durations in LEO where ZBO starts to reduce mass are surprisingly low, which could lead to more applications for cryogenic propellants.

The first chart developed, figure 3, is for 2.2m diameter LO₂ tanks. This shows that ZBO storage durations as low as 5 days in LEO save mass when compared to the traditional passive storage approach. The results for methane storage (figure 4) are a little different in that more days are required before ZBO storage reduces mass, 8.5 days, compared to the 5 days for oxygen storage. At first glance, this is not obvious as methane's boiling point is higher than oxygen's, reducing its cooling requirements. However, boil-off mass is also dependent on the inverse of the heat of vaporization; methane's is 2.4 times that of oxygen.

Hydrogen storage takes quite a bit more days in LEO before ZBO is beneficial and also presents a challenge to cryocooler technology and the integration of two-stage cryocoolers. Still, if missions require storage times in excess of 64 days in LEO, ZBO is predicted to save mass (see figure 5).

Liquid xenon storage begins to save mass almost immediately over gaseous xenon storage. Even so, the relatively high density of xenon gas and low quantities needed for electric propulsion complicate the storage design decision.

Figure 6 compiles the results of all propellants considered and shows the effect of size--the larger the tank, the fewer days in LEO when ZBO has reduced mass. While that is the prediction, beware that this analysis uses floating point cryocooler designs and fewer large cryocoolers exist.

One cryocooler issue that could improve the ZBO results is its design. Existing flight cryocooler designs (one of which was incorporated in this analysis) include a small coldhead that cools a plate that mounts to an instrument. As shown herein, the temperature difference between coldhead and the bulk liquid is substantial, causing larger cryocoolers to be used. A design made specifically for cooling-fluid in a propellant tank could reduce this integration

loss. It could involve submersion of the cold portion of the working fluid tube directly into the propellant, eliminating the coldhead and associated loss. Another variation could be the use of the propellant itself as the cryocooler working fluid. Such designs were not considered here but were explored in reference 11.

Summary

NASA is investigating an array of exploration missions and propulsion technologies for our future. Many of those concepts include cryogenic propellants, possibly involving long storage durations. This analysis addresses the storage duration effect on cryogenic thermal storage system performance, with the purpose of possibly minimizing the storage issue. One method worthy of consideration is zero boil-off storage, which has become more interesting because of the tremendous advances in cryocooler technology. This was applied to oxygen, methane, hydrogen, and xenon propellants in tank sizes of 1.2, 2.2, 3.3, 4.4, and 5.5m in diameter. This technology provides mass savings over traditional, passive- only cryogenic storage when mission durations are as short as one week in LEO for oxygen, two weeks for methane, and roughly 2 months for LH2. Cryogenic xenon saves mass over passive storage almost immediately.

References

1. P. Kittel, D. Plachta, "Propellant Preservation for Mars Missions," Advances in Cryogenic Engineering, Vol. 45, presented at the Cryogenic Engineering Conference, Montreal, Canada, July 12-16, 1999.
2. P. Kittel, L. Salerno, D. Plachta, "Cryocoolers for Human and Robotic Missions to Mars," Cryocoolers 10, presented at the 10th International Cryocooler Conference, Monterey, California, May, 1998.
3. T.R.Strobridge, "Cryogenic Refrigeration—An Updated Survey," NBS Tech Note 655 (1974).
4. D.S. Glaister, M. Donabedian, D.G.T. Curran, and T. Davis, "An Overview of the Performance and Maturity of Long Life Cryocoolers for Space Applications," The Aerospace Corp, El Segundo, Report No. TOR-98(1057)-3 (1998).
5. E. Tward, T. Nast, W. Swift, S. Castles, and T. Davis, private communications.
6. E. Kramer, "Cryogenic On-Orbit Liquid Depot-Storage, Acquisition, and Transfer (COLD-SAT) Experiment Conceptual Design and Feasibility Study," NASA TP-3523 (1998).

7. L.J. Poth, J.R. Van Hook, "Control of the Thermodynamic State of Space-Stored Cryogens by Jet Mixing," *J. Spacecraft*, Vol. 9, No.5, May, 1972.
8. C.K. Chan, TRW, private communications.
9. L.J. Hastings, J.J. Martin, "Large-Scale Liquid Hydrogen Testing of a Variable Density Multi-layer Insulation with a Foam Substrate," NASA/TM—2001-211089, June 2001.
10. R.T. Parmley, W.C. Henninger, S.A. Katz, and I. Spradley, "Test and Evaluate Passive Orbital Disconnect Struts," NASA CR-177368 (1985).
11. P.Kittel, "Propellant Preservation Using Re-liquefiers, *Cryogenics* 41 (2001) 841.

REPORT DOCUMENTATION PAGEForm Approved
OMB No. 0704-0188

Public reporting burden for this collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden, to Washington Headquarters Services, Directorate for Information Operations and Reports, 1215 Jefferson Davis Highway, Suite 1204, Arlington, VA 22202-4302, and to the Office of Management and Budget, Paperwork Reduction Project (0704-0188), Washington, DC 20503.

1. AGENCY USE ONLY (Leave blank)		2. REPORT DATE June 2003	3. REPORT TYPE AND DATES COVERED Technical Memorandum	
4. TITLE AND SUBTITLE An Updated Zero Boil-Off Cryogenic Propellant Storage Analysis Applied to Upper Stages or Depots in an LEO Environment			5. FUNDING NUMBERS WU-706-87-13-00	
6. AUTHOR(S) David Plachta and Peter Kittel				
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES) National Aeronautics and Space Administration John H. Glenn Research Center at Lewis Field Cleveland, Ohio 44135-3191			8. PERFORMING ORGANIZATION REPORT NUMBER E-13421	
9. SPONSORING/MONITORING AGENCY NAME(S) AND ADDRESS(ES) National Aeronautics and Space Administration Washington, DC 20546-0001			10. SPONSORING/MONITORING AGENCY REPORT NUMBER NASA TM-2003-211691 AIAA-2002-3589	
11. SUPPLEMENTARY NOTES Prepared for the 38th Joint Propulsion Conference and Exhibit cosponsored by AIAA, ASME, SAE, and ASEE, Indianapolis, Indiana, July 7-10, 2002. David Plachta, NASA Glenn Research Center, and Peter Kittel, NASA Ames Research Center, Moffett Field, California 94035-1000. Responsible person, David Plachta, organization code 5870, 216-977-7126.				
12a. DISTRIBUTION/AVAILABILITY STATEMENT Unclassified - Unlimited Subject Categories: 16, 20 and 28 Available electronically at http://gltrs.grc.nasa.gov This publication is available from the NASA Center for AeroSpace Information, 301-621-0390.			12b. DISTRIBUTION CODE	
13. ABSTRACT (Maximum 200 words) Previous efforts have shown the analytical benefits of zero boil-off (ZBO) cryogenic propellant storage in launch vehicle upper stages of Mars transfer vehicles for conceptual Mars Missions. However, recent NASA mission investigations have looked at a different and broad array of missions, including a variety of orbit transfer vehicle (OTV) propulsion concepts, some requiring cryogenic storage. For many of the missions, this vehicle will remain for long periods (greater than one week) in low earth orbit (LEO), a relatively warm thermal environment. Under this environment, and with an array of tank sizes and propellants, the performance of a ZBO cryogenic storage system is predicted and compared with a traditional, passive-only storage concept. The results show mass savings over traditional, passive-only cryogenic storage when mission durations are less than one week in LEO for oxygen, two weeks for methane, and roughly 2 months for LH ₂ . Cryogenic xenon saves mass over passive storage almost immediately.				
14. SUBJECT TERMS Cryogenics; Cryocoolers; Thermosyphons; Zero boil-off; Low-earth orbit; Orbit transfer vehicles; Propellant depots; Long-term propellant storage			15. NUMBER OF PAGES 14	
			16. PRICE CODE	
17. SECURITY CLASSIFICATION OF REPORT Unclassified	18. SECURITY CLASSIFICATION OF THIS PAGE Unclassified	19. SECURITY CLASSIFICATION OF ABSTRACT Unclassified	20. LIMITATION OF ABSTRACT	